

**X422 Print Cartridge**

Printer: X422

Declaration of Yield: **Average Cartridge Yield 6000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 7414  
**Std Dev** 366  
**90% Lower Confidence** 7224

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested** start 8-Dec-2004 stop 10-Dec-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low
	2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	9.2
Operating system	Windows 2000
Application software	Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAK041810182	8907BZX	74	74	74	48	48	48	7,618	Y
CAK043000513	8907BZG	74	74	74	48	48	48	6,852	Y
CAK043000663	8907BZC	74	74	74	48	48	48	7,212	Y
CAK043000564	8907BYN	74	74	74	48	48	48	6,933	Y
CAK043000634	8907BZX	74	74	74	48	48	48	7,901	Y
CAK041810175	8907BZG	74	74	74	48	48	48	7,946	Y
CAK043000600	8907BZC	74	74	74	48	48	48	7,496	Y
CAK043000638	8907BYN	74	74	74	48	48	48	7,124	Y
CAK043000636	8907BZX	74	74	74	48	48	48	7,242	Y
CAK043000649	8907BZG	74	74	74	48	48	48	7,684	Y
CAK041810196	8907BZC	74	74	74	48	48	48	7,722	Y
CAK043000673	8907BYN	74	74	74	48	48	48	7,232	Y

Comments and or exceptions: