

**E340-E342n Yield Print Cartridge**

Printer: E340-E342n

Declaration of Yield:

<b>Average Cartridge Yield</b>	<b>2500</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 3036  
**Std Dev** 179  
**90% Lower** 2944  
**Confidence**

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
<b>Date tested</b>	14-Jul-2005	14-Jul-2005
Number of cartridges in testing		12
Qty. of cartridges used in calculation		12
Shake Procedure	1st shake 2nd shake	At toner low At fade
Print mode		Continuous
Number of printers tested		4
Media used		Boise Cascade - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		E340-E342n G10
Operating system		Windows 2000 Service Pack 4
Application software		Acrobat version 7.0.2
Test page version		19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature (C / F)			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAC051740210	MDT2122	25 / 77	25 / 77	24 / 76	51	52	50	3,080	Y
CAC051740207	MDT2091	25 / 77	25 / 77	24 / 76	51	52	50	3,021	Y
CAC051740223	MDT2104	25 / 77	25 / 77	24 / 76	51	52	50	3,151	Y
CAC051740222	MDT2161	25 / 77	25 / 77	24 / 76	51	52	50	3,190	Y
CAC051740093	MDT2122	24 / 76	25 / 77	23 / 74	55	58	51	3,141	Y
CAC051740094	MDT2091	24 / 76	25 / 77	23 / 74	55	58	51	3,021	Y
CAC051740103	MDT2104	24 / 76	25 / 77	23 / 74	55	58	51	3,211	Y
CAC051740100	MDT2161	24 / 76	25 / 77	23 / 74	55	58	51	3,251	Y
CAC051740227	MDT2122	24 / 76	24 / 76	24 / 76	54	55	53	2,620	Y
CAC051740095	MDT2091	24 / 76	24 / 76	24 / 76	54	55	53	2,928	Y
CAC051740219	MDT2104	24 / 76	24 / 76	24 / 76	54	55	53	2,848	Y
CAC051740228	MDT2161	24 / 76	24 / 76	24 / 76	54	55	53	2,974	Y

**Comments and or exceptions:**

Also covers the following part number(s):

24015SA	24036SE	34237HR
24016SE	24038SL	SWE2500
24018SL	34217HR	