

Optra M410/M412 High Yield Print Cartridge

Printer: Optra M410

Declaration of Yield: **Average Cartridge Yield 15000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 17515
Std Dev 2094
90% Lower Confidence 16429

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 6-Dec-2004 stop 14-Dec-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAZ042740860	2546161	74	75	74	48	48	48	13,984	Y
CAZ041317698	2546164	74	75	74	48	48	48	17,469	Y
CAZ041940143	2546156	74	75	74	48	48	48	17,729	Y
CAZ042740854	2546499	74	75	74	48	48	48	14,266	Y
CAZ042740853	2546161	74	74	74	48	49	48	14,977	Y
CAZ041100051	2546164	74	74	74	48	49	48	20,477	Y
CAZ041317714	2546156	74	74	74	48	49	48	17,442	Y
CAZ041940105	2546499	74	74	74	48	49	48	18,072	Y
CAZ041940277	2546161	74	74	74	48	49	48	18,409	Y
CAZ041100020	2546164	74	74	74	48	49	48	19,624	Y
CAZ041100014	2546156	74	74	74	48	49	48	19,474	Y
CAZ041317726	2546499	74	74	74	48	49	48	18,252	Y

Comments and or exceptions:

