

**T420 High Yield Print Cartridge**

Printer: T420

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>10000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 11590  
**Std Dev** 535  
**90% Lower Confidence** 11313

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      start 28-Nov-2004      stop 1-Dec-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low
	2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.01
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAD040833059	890680X	74	75	74	48	49	48	11,208	Y
CAD040947631	89000VG	74	75	74	48	49	48	12,314	Y
CAD041030019	89000WG	74	75	74	48	49	48	12,108	Y
CAD040944006	8906812	74	75	74	48	49	48	12,382	Y
CAD041030007	890680X	74	75	74	48	48	48	11,694	Y
CAD040830800	89000VG	74	75	74	48	48	48	10,748	Y
CAD040944312	89000WG	74	75	74	48	48	48	11,269	Y
CAD041030042	8906812	74	75	74	48	48	48	12,013	Y
CAD041030073	890680X	74	75	74	48	48	47	11,671	Y
CAD040948372	89000VG	74	75	74	48	48	47	11,556	Y
CAD040830838	89000WG	74	75	74	48	48	47	11,062	Y
CAD040945141	8906812	74	75	74	48	48	47	11,052	Y

**Comments and or exceptions:**