

T520/T522 Print Cartridge

Printer: T520

Declaration of Yield: **Average Cartridge Yield 20000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 21502
Std Dev 538
90% Lower Confidence 21223

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 17-Jan-2005 stop 21-Jan-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 5
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity				
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min	Cartridge Yield	Cart used in Calculation
CAX043501FD1D	A001990	74	75	74	48	51	48	21,163	Y
CAX043501FD4D	A001887	74	75	74	48	51	48	20,799	Y
CAX0435109ADD	A001871	74	75	74	48	51	48	20,764	Y
CAX04351097ED	A001875	74	75	74	48	51	48	20,992	Y
CAX04351088CD	A001990	74	75	74	48	49	48	21,863	Y
CAX0435204B9D	A001887	74	75	74	48	49	48	22,475	Y
CAX04350128ED	A001871	74	75	74	48	49	48	21,781	Y
CAX04351088BD	A001875	74	75	74	48	49	48	21,854	Y
CAX0435204BCD	A001990	74	75	74	48	49	48	21,305	Y
CAX043511A6BD	A001887	74	75	74	48	49	48	21,627	Y
CAX0435204BBD	A001871	74	75	74	48	49	48	21,275	Y
CAX043501FDFD	A001875	74	75	74	48	49	48	22,127	Y