

T620/T622 Print Cartridge

Printer: T622

Declaration of Yield:

Average Cartridge Yield	30000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 34943
Std Dev 1913
90% Lower Confidence 33951

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start stop
 19-Jan-2005 27-Jan-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low
	2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 5
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity				
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min	Cartridge Yield	Cart used in Calculation
CAX043500ED8	N5780150	74	75	74	48	49	48	35,101	Y
CAX043500EE2	41MF623	74	75	74	48	49	48	32,942	Y
CAX043511B28	41ZT414	74	75	74	48	49	48	34,534	Y
CAX0435204C1	41ZT513	74	75	74	48	49	48	33,626	Y
CAX043510E58	N5780150	74	75	74	48	49	48	37,550	Y
CAX043511B29	41MF623	74	75	74	48	49	48	33,994	Y
CAX0435204C2	41ZT414	74	75	74	48	49	48	32,202	Y
CAX043510E5F	41ZT513	74	75	74	48	49	48	37,125	Y
CAX043500FE8	N5780150	74	75	74	48	49	48	38,358	Y
CAX043510E55	41MF623	74	75	74	48	49	48	33,371	Y
CAX043500FE9	41ZT414	74	75	74	48	49	48	35,197	Y
CAX0435022F9	41ZT513	74	75	74	48	49	48	35,313	Y