

T630, T632, T634 Print Cartridge

Printer: T634

Declaration of Yield: **Average Cartridge Yield 5000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 6111
Std Dev 252
90% Lower Confidence 5981

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 28-Sep-2004 stop 29-Sep-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX042028316D	9914W1H	75	75	74	51	52	51	6,213	Y
CAX042066315D	9914W5W	75	75	74	51	52	51	5,942	Y
CAX041658882D	9914W6Y	75	75	74	51	52	51	6,262	Y
CAX041638478D	9914W10	75	75	74	51	52	51	5,859	Y
CAX041639137D	9914W1H	75	75	75	51	51	51	5,775	Y
CAX042028249D	9914W5W	75	75	75	51	51	51	6,372	Y
CAX042066328D	9914W6Y	75	75	75	51	51	51	5,870	Y
CAX041658909D	9914W10	75	75	75	51	51	51	6,413	Y
CAX041658070D	9914W1H	75	75	75	51	51	51	6,003	Y
CAX041638434D	9914W5W	75	75	75	51	51	51	6,431	Y
CAX042029567D	9914W6Y	75	75	75	51	51	51	6,349	Y
CAX042066999D	9914W10	75	75	75	51	51	51	5,846	Y

Comments and or exceptions: