

**X422 High Yield Print Cartridge**

Printer: X422

Declaration of Yield: **Average Cartridge Yield 12000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 14410  
**Std Dev** 468  
**90% Lower Confidence** 14167

**For questions concerning testing contact:**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

**Date tested** start 4-Dec-2004 stop 7-Dec-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	9.2
Operating system	Windows 2000
Application software	Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAK042320301	8907BZX	74	75	74	48	48	48	14,513	Y
CAK042320314	8907BZG	74	75	74	48	48	48	14,670	Y
CAK042320296	8907BZC	74	75	74	48	48	48	13,987	Y
CAK042320279	8907BYN	74	75	74	48	48	48	13,694	Y
CAK042320283	8907BZX	74	75	74	48	48	48	14,852	Y
CAK042320307	8907BZG	74	75	74	48	48	48	15,041	Y
CAK042320305	8907BZC	74	75	74	48	48	48	15,173	Y
CAK042320302	8907BYN	74	75	74	48	48	48	13,942	Y
CAK042320291	8907BZX	74	75	74	48	48	48	14,272	Y
CAK042320261	8907BZG	74	75	74	48	48	48	14,567	Y
CAK042320323	8907BZC	74	75	74	48	48	48	14,192	Y
CAK042320247	8907BYN	74	75	74	48	48	48	14,012	Y

Comments and or exceptions: