

**X830e/X832e Print Cartridge**

Printer: X830e

Declaration of Yield: **Average Cartridge Yield 30000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 33157  
**Std Dev** 906  
**90% Lower Confidence** 32596

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**start** 8-Jun-2004 **stop** 14-Jun-2004

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade X-9000 - 20# - Lett
Paper feed orientation	Short Edge Feed (SEF)
Driver version	W820 Driver Version 7.4.1
Operating system	Windows 2000 SP4
Application software	Acrobat version 6.01
Test page version	Standard_Testpage_(19752_2004).pdf

Cartridge testing data:	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
J0-80507-4517K30	01-65579	74	74	73	58	60	57	34,014	y
J0-80509-4517K30	01-65601	74	74	73	58	60	57	33,074	y
J0-80510-4517K30	01-52970	74	74	73	58	60	57	32,494	y
J0-80505-4517K30	01-65579	74	75	73	58	61	57	32,730	y
J0-80512-4517K30	01-65601	74	75	73	58	61	57	32,330	y
J0-80508-4517K30	01-52970	74	75	73	58	61	57	31,931	y
J3-80782-4423K30	01-65579	73	74	72	60	63	59	34,451	y
J3-80773-4423K30	01-65601	73	74	72	60	63	59	34,311	y
J3-80803-4423K30	01-52970	73	74	72	60	63	59	33,081	y

**Comments and or exceptions:**